| | |
|---|---|
| **SYSTEM NO.** | SSXAU784 |
| **DESCRIPTION** | Cat-back |
| **NOTES** | |

## PARTS REQUIRED

| PART NO. | DESCRIPTION | QUANTITY | IN PACKAGE |
|---|---|---|---|
| **MSAU619** | **Rear Silencer Assembly {valve motor from the OE exhaust is required for fitment}** | **1** | |
| CHC79SS | 79mm Band Clamp - 304 S/S | 1 | |
| F3160 | Wire Formed Spring Assembly | 2 | |
| M5FLGNUT | M5 X 0.8 Nylon Coat Flange Nut | 6 | |
| **MSAU622** | **Centre Silencer** | **1** | |
| CHC68SS | 68mm Band Clamp - 304 S/S | 1 | |
| CHC79SS | 79mm Band Clamp - 304 S/S | 1 | |
| F20050 | 5.0mm Spacer | 2 | |
| F5125 | Adaptor Sleeve 76.2mm 1.5 304 X 170 (65 Id) | 1 | |
| **MSTIP166** | **Polished Tip Assembly** | **4** | |
| CHC66.5SS | 66.5mm Band Clamp-304 S/Steel | 4 | |

MILLTEK

## TECHNICAL INFORMATION

| NOTES | OE rear silencer hanger brackets need to be rotated 180° as per below images: |
|---|---|

OE Position:



Rotated 180°:

