SYSTEM NO.	SSXAU984
DESCRIPTION	Cat-back
NOTES	

PARTS REQUIRED

PART NO.	DESCRIPTION	QUANTITY	IN PACKAGE
MSAU718	**Trim Connecting Pipe**	**2**	
CHC73SS	73mm Band Clamp 304 S/Steel	2	
MSAU764REP	**Centre Silencer Replacement Pipe (80mm Version)**	**1**	
CHC68SS	68mm Band Clamp - 304 S/S	2	
F20050	5.0mm Spacer	2	
MSAU766	**LH Valved Outlet Pipe**	**1**	
6MMSPRING	6mm S/Steel Spring Washer	3	
CHC66.5SS	66.5mm Band Clamp-304 S/Steel	1	
CHC73SS	73mm Band Clamp 304 S/Steel	1	
M6NYLOC	M6 Nyloc Nutbzp	3	
M6X16BUTT	M6 X 16mm Socket Button Head	3	
MSAU767	**RH Valved Outlet Pipe**	**1**	
6MMSPRING	6mm S/Steel Spring Washer	3	
CHC66.5SS	66.5mm Band Clamp-304 S/Steel	1	
CHC73SS	73mm Band Clamp 304 S/Steel	1	
M6NYLOC	M6 Nyloc Nutbzp	3	
M6X16BUTT	M6 X 16mm Socket Button Head	3	
MSAU827	**Race Rear Silencer**	**1**	
CHC83SS	83mm Band Clamp - 304 S/S	1	
MSTIP255	**LH Titanium Oval Trim (170x107)**	**1**	
CHC73SS	73mm Band Clamp 304 S/Steel	1	
MSTIP256	**RH Titanium Oval Trim (170x107)**	**1**	
CHC73SS	73mm Band Clamp 304 S/Steel	1	

MILLTEK

TECHNICAL INFORMATION

NOTES	OE rear silencer hanger brackets need to be rotated 180° as per below images:

OE Position:



Rotated 180°:

